

HC-3518 高速离心机

High speed centrifuge



Features:

- ★ Microcomputer control, LCD liquid crystal display (LCD).
- ★ Ac frequency conversion motor drive, quiet operation clean.
- ★ Offers nine ascending and descending rate selection mode; Offer ten kinds of working mode selection, can free programming, call.
- ★ Speed/centrifugal force can be set each other, with the screen display.
- ★ Two optional timing mode: run start timing and timing starts to set speed, easy to switch.
- ★ Door with double lock rod design, magnetic locks, electric door, more safety and reliable operation.

HC-3518 技术指标 Technical data

最高转速 Max speed	21000rpm
最大相对离心力 Max RCF	23198 × g
转速精度 Speed accuracy	±100rpm
噪音 Noise	≤55dB
定时范围 Timer range	1min~99:99:59 (hh: mm: ss)
温升指标 Temperature indicators	≤8℃ (最高转速运行20分钟)
重量 Weight	50kg
电源 Power Supply	AC 220V 50Hz
功率 Power	550VA
外形尺寸 Dimensions(L × W × H)mm	373 × 510 × 405mm (L × W × H)

HC-3518 可选配的转头

转头型号	转头容量	最高转速	离心力
H120.5	12 × 0.5ml	21000rpm	22182 × g
H2402	24 × 1.5ml/2.2ml	16000rpm	20049 × g
H1202	12 × 1.5ml/2.2ml	18000rpm	23198 × g
H1205	12 × 5ml	16000rpm	17459 × g
H1210	12 × 10ml	14000rpm	18188 × g
H480.5	48 × 0.5ml	16000rpm	21504 × g
H3602	36 × 1.5ml/2.2ml	14000rpm	17749 × g
H0815	8 × 15ml	12000rpm	14170 × g
H0485	4 × 100ml	12000rpm	14570 × g
H0650	6 × 50ml	12000rpm	16099 × g
H0685	6 × 100ml	10000rpm	10170 × g
P0485	4 × 85ml	5000rpm	3830 × g

* 转头型号中“H”表示角转头，“P”表示水平转头

HC-3518特性:

- ★ 微电脑控制、LCD液晶显示。
- ★ 交流变频电机驱动，运行宁静清洁。
- ★ 提供9种升、降速率选择模式；提供10种工作模式选择，可自由编程、调用。
- ★ 转速/离心力可相互设定，同步显示。
- ★ 两种计时模式可选：运行开始计时和到达设定转速开始计时，切换方便。
- ★ 门盖采用双锁杆设计，磁感应门锁，电动开门，运行更加安全可靠。
- ★ 运行中可随时更改参数，无需停机。
- ★ 独特的风冷排风设计，温升低、噪音小。
- ★ 自动识别转头。
- ★ 转头使用记忆功能，转头达到使用寿命后机器会报警提示，防止安全隐患。
- ★ Can change at any time in the operation of the parameters without downtime.
- ★ Unique design of air exhaust temperature, low noise.
- ★ Automatic identification of 9. Turn.
- ★ Turned to use memory function, turned to the service life of the machine will alarm prompt, prevent the security hidden danger.