


KDC-1044L 大容量低速离心机

Low speed centrifuge



特性:

低速离心机

- ★ 微电脑控制、LCD 液晶显示
- ★ 交流变频电机驱动，运行宁静清洁
- ★ 提供 9 种升、降速率选择模式；提供 10 种工作模式选择，可自由编程、调用
- ★ 转速 / 离心力可相互设定、同步显示
- ★ 两种计时模式可选：运行开始计时和到达设定转速开始计时，切换方便
- ★ 门盖双挂杆设计、磁感应门锁，电动开门，运行更加安全可靠
- ★ 离心偏重容忍度最大可达 30 克，无需专门称重配平
- ★ 运行中可随时更改参数，无需停机
- ★ 独特的风冷排风设计，温升低、噪音小。

KDC-1044L 可选配的转头、提篮				
序号	转头、吊杯	最高转速 (rpm)	最大离心力 (×g)	主机
NO.1	水平转头	4500	3387	4 × 600ml (圆吊杯)
1	提篮	4200	3387	16 × 50ml
2	提篮			76 × 10ml
3	提篮			96 × 真空采血管
4	提篮			4 × 250ml
5	提篮			12 × 100ml
6	提篮			40 × 15ml (尖底带盖)
7	提篮			148 × 5ml (放免管)
NO.2	水平转头	4500	3321	148 × 真空采血管 (蜂窝吊杯)

Features:

- ★ Microcomputer control, LCD liquid crystal display(LCD).
- ★ Ac frequency conversion motor drive, quiet operation clean.
- ★ Offers nine ascending and descending rate selection mode; Offer ten kinds of working mode selection ,can free programming call.
- ★ Speed/centrifugal force can be set and double synchronous display screen.
- ★ Two optional timing mode: run start timing and timing starts to set speed, easy to switch.
- ★ Door with double lock rod design, magnetic locks, electric door, more safety and reliable operation.
- ★ Centrifugal lay particular stress on tolerance up to 30 grams, no special load balancing.
- ★ Can change at any time in the operation of the parameters without downtime
- ★ Unique design of air exhaust temperature, low noise.

KDC-1044L 技术指标

最高转速Max speed	4200rpm
最大相对离心力Max RCF	3387 × g
转速精度Speed accuracy	± 10rpm
转子最大容量Rotor capacity	600ml × 4
温升指标Temperature rise	≤10°C (运行 20 分钟)
噪音Noise	≤55dB
定时范围Timer range	1min ~ 99:99:59 (hh:mm:ss) / 连续 / 短时离心
结构Construction	钢制结构, 不锈钢离心腔
重量Weight	90kg
外形尺寸Dimensions	580 × 740 × 890mm (L × W × H)