HC-3016R 高速冷冻离心机

High speed refrigerated centrifuge

HC-3016R特性：

★ 微电脑控制、LCD液晶显示。
★ 采用交流变频电机驱动。
★ 进口制冷压缩机。
★ 9种升、降速率选择。
★ 10种自定义工作模式选择。
★ 转速/离心力互设、同步显示。
★ 全钢制结构，不锈钢离心腔。
★ 运行中可随时更改参数，无需停机。
★ 门盖采用双锁杆设计，磁感应门锁，电动开门，运行更加安全可靠。
★ 自动平衡，无需配平。
★ 自动识别转子。
★ 转头使用记忆功能，转头达到使用寿命后机器会报警提示，防止安全隐患。
★ 两种计时模式可选：运行开始计时和到达设定转速开始计时，切换方便。

HC-3016R 技 术 指 标 Technical data	
最高转速 Max speed	18000rpm
最大相对离心力 Max RCF	23846× g
转速精度 Speed accuracy	±100rpm
温控范围 Temperature range	-20℃~40℃
温控精度 Temperature accuracy	±2℃
噪音 Noise	≤55dB
定时范围 Timer range	1min~99:99:59（hh：mm：ss）
结构 Construction	钢制结构，不锈钢离心腔
重量 Weight	90kg
电源 Power Supply	AC 220V 50Hz
功率 Power	1.3kVA
外形尺寸 Dimensions(L×W×H)mm	585×580×500

Features:

★ Microcomputer control, LCD liquid crystal display (LCD).
★ driven by ac frequency conversion motor.
★ imported refrigeration compressor.
★ 9 kinds of ascending and descending rate of choice.
★ 10 kinds of custom work mode selection.
★ speed mutually establish/centrifugal force, synchronous display.
★ full steel structure, stainless steel centrifugal cavity.
★ can change at any time in the operation of the parameters, without downtime.
★ door with double lock rod design, magnetic locks, electric door, more safety and reliable operation.
★ automatic balance without balancing.
★ automatic identification of rotor.
★ turned to use memory function, turned to the service life of the machine after alarm prompt, prevent the security hidden danger.
★ two optional timing mode: run start timing and timing starts to set speed, easy to switch.

HC-3016R 可选配的转头

转头型号	最高转速	最大离心力	转头容量
H240.2	18000rpm	18824×g	24×0.2ml
H120.5	18000rpm	16300×g	12×0.5ml
H240.5	18000rpm	23846×g	24×0.5ml
H1202	18000rpm	23198×g	12×1.5ml /2.2ml
H2402	14000rpm	17465×g	24×1.5ml /2.2ml
H1205	16000rpm	17459×g	12×5ml
H1207	14000rpm	16327×g	12×7ml
H1210	12000rpm	13363×g	12×10ml
H0815	12000rpm	14107×g	8×15ml
H0650	12000rpm	16099×g	6×50ml
H320.2	14000rpm	13367×g	32×0.2ml(PCR八联排）

TEL：400-888-2987