



集热式智能搅拌器

Intelligent agitator with heat collection

SY20-2



技术参数 Technical parameters

电源: Power:	AC220V±10% 50Hz	控温精度: The temperature control accuracy:	±0.5℃
电机功率: Motor power:	20W	超温保护: Overtemperature protection:	≥ 340℃
电机转矩: Motor torque:	40mN·M	加热速率: Heating rate:	4.5k/min
搅拌点位数: Number of stirring points:	1	工作盘材质: Work plate material:	不锈钢锅 Stainless steel pot
最大容积: Maximum volume:	5000ml	不锈钢容器尺寸: Stainless steel Container Size:	φ240x139.5mm
最大搅拌容量(水): Maximum stirring capacity:	20~3000ml	传感器: Sensors:	PT100
搅拌转速: Stirring speed:	50-2000r/min	外壳防护等级: Housing protection class:	IP21
加热功率: Heating power:	1000W	重量: Weight:	6KG
温度、转速显示: Temperature, speed display:	数码管 Digital tube	外形尺寸: Dimension:	260x320x270mm (不包括表杆)
加热温度范围: Heating temperature range:	室温 ~330℃ Room temperature ~330℃	允许环境温度: Allowable ambient temperature:	0~40℃
液体温度范围: Liquid temperature range:	室温 ~250℃ At room temperature to 250℃	允许相对湿度: Allowable relative humidity:	80%
附件: 5 升不锈钢容器1个, 容器盖1个, 长短表杆各1根, PT100 传感器 1 支, 传感器支架 1 个, 搅拌子 1 个。 Attachment: One 5-liter stainless steel container, one container cover, one long and short meter rod each, 1 PT100 sensor, 1 sensor bracket, one agitator.			

智能磁力搅拌加热锅

Intelligent magnetic stirring heating pot

SY18-1



技术参数 Technical parameters

电源: Power:	AC220V±10% 50Hz	控温精度: The temperature control accuracy:	±0.1℃
电机功率: Motor power:	20W	超温保护: Overtemperature protection:	≥ 340℃
电机转矩: Motor torque:	40mN·M	加热速率: Heating rate:	4.8k/min
搅拌点位数: Number of stirring points:	1	定时时间: Timing Time:	0-9999min
最大容积: Maximum volume:	500ml	加热锅尺寸: Stainless steel Container Size:	φ134x70mm
最大搅拌容量(水): Maximum stirring capacity:	20~500ml	传感器: Sensors:	PT100
搅拌转速: Stirring speed:	50-2000r/min	外壳防护等级: Housing protection class:	IP21
加热功率: Heating power:	600W	重量: Weight:	3.7KG
温度、转速显示: Temperature, speed display:	数码管 Digital tube	外形尺寸: Dimension:	260x160x110mm (不包括表杆)
加热温度范围: Heating temperature range:	室温 ~330℃ Room temperature ~330℃	允许环境温度: Allowable ambient temperature:	0~40℃
液体温度范围: Liquid temperature range:	室温 ~250℃ At room temperature to 250℃	允许相对湿度: Allowable relative humidity:	80%
附件: 长短表杆各1根, 温度传感器及支架1套, 搅拌子1个, 变向多用夹1个。 Attachment: One long meter rod, one temperature sensor and one set of support, one multi-purpose clamp in the direction of change.			

