



卧式恒速电动搅拌器

HORIZONTAL CONSTANT SPEED ELECTRIC MIXER



HD2010W(100W)

HD2004W(40W)

HD2015W(150W)

▶ 技术参数

Technical parameters

	HD2015W(150W)	HD2010W(100W)	HD2004W(40W)
电源: Power:	AC220V±10%	AC220V±10%	AC220V±10%
控制操作方式: Control mode of operation:	按键 Keystroke	按键 Keystroke	按键 Keystroke
电机功率: Motor power:	150W	100W	40W
电机转矩: Motor torque:	0.8N·M	0.6N·M	0.3N·M
转速控制: Speed control:	无极 Infinity	无极 Infinity	无极 Infinity
速度显示: Speed display:	液晶 Liquid crystal	液晶 Liquid crystal	液晶 Liquid crystal
转速: Speed of revolution:	20-1300r/min	20-1300r/min	20-1600r/min
适用介质粘度: Applicable medium viscosity:	10000mpas	5000mpas	10000mpas
搅拌容量(水): Maximum stirring capacity:	200~30000ml	200~20000ml	200~10000ml
定时时间: Timing Time:	0-9999min	0-9999min	0-9999min
转夹头夹持范围最小直径: Minimum diameter of clamping range of rotary chuck:	0.5mm	0.5mm	0.5mm
转夹头夹持范围最大直径: Maximum diameter of clamping range of rotary chuck:	13mm	13mm	10mm
延长臂直径: Extension arm diameter:	14mm	14mm	14mm
延长臂长度: Extension arm length:	180mm	180mm	160mm
重量: Weight:	12KG	10.5KG	10KG
外形尺寸: Dimension:	320x220x770mm	320x220x770mm	320x220x770mm
允许环境温度: Allowable ambient temperature:	0~40°C	0~40°C	0~40°C
允许相对湿度: Allowable relative humidity:	80%	80%	80%
标配搅拌桨: 十字型不锈钢搅拌桨 Standard mixing paste: Cross type		标配搅拌桨: 四氟搅拌桨 Standard mixing paste: tetrafluorobal stirring paddle	

优点: 恒速电动搅拌器采用深度闭环,所以在低速时能在恒功率工作; 调速采用轻触开关,可逆转搅拌。
Advantages: constant speed electric mixer adopts deep closed loop, so at low speed it can work at constant power. The speed adjustment adopts the lighttouch switch, which can reverse stirring.

备注: 转速显示: 液晶屏上行测得转速,下行为转向和设定转速。
Note: Speed display: the LCD can measure the speed on the upward side, and turn and set the speed on the downward side.

D系列电动搅拌器

D SERIES ELECTRIC STIRRER



D2004W(40W)

D2010W(100W)

D2015W(150W)

▶ 技术参数

Technical parameters

	D2015W(150W)	D2010W(100W)	D2004W(40W)
电源: Power:	AC220V±10%	AC220V±10%	AC220V±10%
控制操作方式: Control mode of operation:	旋钮 Knob	旋钮 Knob	旋钮 Knob
电机功率: Motor power:	150W	100W	40W
电机转矩: Motor torque:	0.8N·M	0.6N·M	0.3N·M
转速控制: Speed control:	无极 Infinity	无极 Infinity	无极 Infinity
速度显示: Speed display:	数码管 Digital tube	数码管 Digital tube	数码管 Digital tube
转速: Speed of revolution:	20-1300r/min	20-1300r/min	20-1600r/min
适用介质粘度: Applicable medium viscosity:	10000mpas	5000mpas	10000mpas
搅拌容量(水): Maximum stirring capacity:	200~30000ml	200~20000ml	200~10000ml
转夹头夹持范围最小直径: Minimum diameter of clamping range of rotary chuck:	0.5mm	0.5mm	0.5mm
转夹头夹持范围最大直径: Maximum diameter of clamping range of rotary chuck:	13mm	13mm	10mm
延长臂直径: Extension arm diameter:	14mm	14mm	14mm
延长臂长度: Extension arm length:	180mm	180mm	160mm
重量: Weight:	12KG	10.5KG	10KG
外形尺寸: Dimension:	320x220x770mm	320x220x770mm	320x220x770mm
允许环境温度: Allowable ambient temperature:	0~40°C	0~40°C	0~40°C
允许相对湿度: Allowable relative humidity:	80%	80%	80%
标配搅拌桨: 十字型不锈钢搅拌桨 Standard mixing paste: Cross type		标配搅拌桨: 四氟搅拌桨 Standard mixing paste: tetrafluorobal stirring paddle	

优点: 无刷直流电机驱动,转速显示,旋钮调速。
Merit:Brushless de motor driven,Rotational speed,Knob speed.