

数显恒温磁力搅拌器

DIGITAL DISPLAY THERMOSTATIC MAGNETIC STIRRER



► 技术参数 Technical parameters

B11-2B11-3

电源: Power:	AC220V±10% 50Hz	AC220V±10% 50Hz
电机功率: Motor power:	20W	20W
电机转矩: Motor torque:	40mN·M	40mN·M
搅拌点位数: Number of stirring points:	1	1
最大搅拌容量(水): Maximum stirring capacity:	20~10000ml	20~10000ml
搅拌转速: Stirring speed:	50-2000r/min	50-2000r/min
加热功率: Heating power:	600W	600W
转速数显: Speed digital display:	数码管 Digital tube	/
温度数显: Temperature digital display:	/	数码管 Digital tube
加热温度范围: Heating temperature range:	室温 ~340℃ (超温保护 400℃) Room temperature ~340℃ (over temperature protection 400℃)	室温 ~340℃ (超温保护 400℃) Room temperature ~340℃ (over temperature protection 400℃)
液体温度范围: Liquid temperature range:	室温 ~250℃ At room temperature to 250℃	室温 ~250℃ At room temperature to 250℃
控温精度: The temperature control accuracy:	±1℃	±1℃
加热速率: Heating rate:	100k/min	100k/min
工作盘材质: Work plate material:	不锈钢镀黑 Stainless steel blackening	不锈钢镀黑 Stainless steel blackening
加热盘尺寸: Heating disk size:	φ140mm	φ140mm
传感器: Sensors:	/	PT100
外壳防护等级: Housing protection class:	IP21	IP21
重量: Weight:	3.3KG	3.3KG
外形尺寸: Dimension:	280x160x110mm (不包括表杆)	280x160x110mm (不包括表杆)
允许环境温度: Allowable ambient temperature:	0~40℃	0~40℃
允许相对湿度: Allowable relative humidity:	80%	80%
附件: 长、短表杆各1根, 搅拌子1个。 Attachment: Long, short table rod each one, stirring one.		



数显恒温磁力搅拌器

DIGITAL DISPLAY THERMOSTATIC MAGNETIC STIRRER



► 技术参数 Technical parameters

S10-2S10-3

电源: Power:	AC220V±10% 50Hz	AC220V±10% 50Hz
电机功率: Motor power:	20W	20W
电机转矩: Motor torque:	80mN·M	80mN·M
搅拌点位数: Number of stirring points:	1	1
最大搅拌容量(水): Maximum stirring capacity:	20000ml	20000ml
搅拌转速: Stirring speed:	50-2000r/min	50-2000r/min
加热功率: Heating power:	800W	800W
转速数显: Speed digital display:	/	数码管 Digital tube
温度数显: Temperature digital display:	数码管 Digital tube	数码管 Digital tube
加热温度范围: Heating temperature range:	室温 ~340℃ (超温保护 400℃) Room temperature ~340℃ (over temperature protection 400℃)	室温 ~340℃ (超温保护 400℃) Room temperature ~340℃ (over temperature protection 400℃)
液体温度范围: Liquid temperature range:	室温 ~250℃ At room temperature to 250℃	室温 ~250℃ At room temperature to 250℃
控温精度: The temperature control accuracy:	±1℃	±1℃
加热速率: Heating rate:	75k/min	75k/min
工作盘材质: Work plate material:	不锈钢镀黑 Stainless steel blackening	不锈钢镀黑 Stainless steel blackening
加热盘尺寸: Heating disk size:	φ170mm	φ170mm
传感器: Sensors:	PT100	PT100
外壳防护等级: Housing protection class:	IP21	IP21
重量: Weight:	4.4KG	4.4KG
外形尺寸: Dimension:	330x195x125mm (不包括表杆)	330x195x125mm (不包括表杆)
允许环境温度: Allowable ambient temperature:	0~40℃	0~40℃
允许相对湿度: Allowable relative humidity:	80%	80%
附件: 长、短表杆各1根, 温度传感器及支架1套, 搅拌子1个。 Attachment: Long,short watch rod one, Temperature sensor and bracker one Stir the particles.		